



TECHNICAL DATASHEET

RAPTOR MICRO PRIMER

Product information:

Allround drypfri grunder til grundning før malerarbejde.

Application:

Anvendes udendørs og indendørs på beton, puds, letbeton, eternit, sandspartel, gipskarton samt fiberplader før slutbehandling. Endvidere velegnet som støvbindende behandling på betongulve.

Painting instructions:

Application method: Roler, brush or spraypaint

Coverage: 7-9 m² per liter

Temperature: min. +5°

Touch Dry: approx. 1h at 20°*

Drying Time: approx. 2h at 20°*

Tools: clean with water

Ingen risiko for dampe ved indånding. Uden nævneværdig risiko ved kontakt med huden og øjnene eller ved indtagelse. Dog er der risiko ved indånding af spraydampe, støvskyer m.m. – brug støvmaske.

Storage:

Store dry, cold but frost free. Replace lid firmly to ensure an airtight seal. Remove as much paint as possible from decorating tools before cleaning in warm water. Do not empty surplus paint into drains or watercourses. Local authorities have special facilities for the disposal of waste coatings, paint and old buckets.

Inholders/ Preservation:

Benz-/methyl-/chlormethyl-isothiazolinon. Can cause an allergic reaction (preservation).

Sonstige Informationen:

- **EU limit value** for this product (Cat A/h): 30g/l (2010).
This product contains max 1 g/l VOC.
- (*) depending of air conditions